

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
24 January 2002 (24.01.2002)


PCT

(10) International Publication Number
WO 02/06857 A1

- (51) International Patent Classification⁷: G01V 11/00
- (21) International Application Number: PCT/GB01/03042
- (22) International Filing Date: 6 July 2001 (06.07.2001)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
0017227.0 14 July 2000 (14.07.2000) GB
- (71) Applicant (for all designated States except CA, FR, US):
SCHLUMBERGER EVALUATION & PRODUCTION
SERVICES (UK) LIMITED [GB/GB]; 8th Floor, South
Quay Plaza 2, 183 Marsh Wall, London E14 9SH (GB).
- (71) Applicant (for CA only): SCHLUMBERGER CANADA
LIMITED [CA/CA]; 24th Floor, Monenco Place, 801 6th
Avenue, S.W., Calgary, Alberta T2P 3W2 (CA).
- (71) Applicant (for FR only): SERVICES PETROLIERS
SCHLUMBERGER [FR/FR]; 42, rue Saint Dominique,
F-75007 Paris (FR).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): STONE, Terry,
Wayne [CA/GB]; 9 Loader Close, Kingsworthy, Hamp-
shire SO23 7TF (GB).
- (74) Agent: STOOLE, Brian, D.; Geco-Prakla (UK) Limited,
Schlumberger House, Buckingham Gate, Gatwick, West
Sussex RH6 0NZ (GB).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ,
DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR,
HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR,
LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ,
NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM,
TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SI, SZ, TZ, UG, ZW), Eurasian
patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European
patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE,
IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF,
CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: METHOD OF DETERMINING SUBSIDENCE IN A RESERVOIR



(57) Abstract: A reservoir simulator first estimates rock displacement parameters (u, v, and w) representing rock movement in the x, y, and z directions. When the rock displacement parameters (u, v, w) are determined, " $\epsilon_{x,y,z}$ " (the X,Y,Z elongation strains) and " $\gamma_{xy,yz,zx}$ " (the shear strains) are determined since " $\epsilon_{x,y,z}$ " and " $\gamma_{xy,yz,zx}$ " are function of "u", "v", and "w". When " $\epsilon_{x,y,z}$ " and " $\gamma_{xy,yz,zx}$ " are determined, " $\sigma_{x,y,z}$ " (the elastic normal rock stress in x,y,z directions) and " $\tau_{xy,yz,zx}$ " (the elastic shear stress) are determined since " $\sigma_{x,y,z}$ " and " $\tau_{xy,yz,zx}$ " are a function of " $\epsilon_{x,y,z}$ " and " $\gamma_{xy,yz,zx}$ ". When " $\sigma_{x,y,z}$ " and " $\tau_{xy,yz,zx}$ " are determined, the rock momentum balance differential equations can be solved, since these equations are a function of " $\sigma_{x,y,z}$ " and " $\tau_{xy,yz,zx}$ ". When any residuals are substantially equal to zero, the estimated rock displacement parameters (u, v, and w) will represent accurate rock displacement parameters for the reservoir. When the rock momentum balance differential equations are solved, the rock displacement parameters (u, v, w), at an advanced time, are known. These rock displacement parameters (u, v, w) represent and characterize a subsidence in a seabed floor because subsidence will result from rock movement; and rock movement will result from a continual withdrawal of oil or other hydrocarbon deposits or other fluids such as water over a period of time from an Earth formation. This abstract of the disclosure is given for the sole purpose of allowing a patent searcher to easily determine the content of the disclosure in this application.

WO 02/06857 A1

[illegible]

— *with international search report*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.